



• Intermediate values available

Wilco Part Number	L uH	Q Nom.	SRF Nom. (MHz)	RDC OHMS Nom.	I (MA) Max	Dia Nom.	Test Freq. (MHz)
L 10 G	1.0	37	257	.22	915	.121	7.9
L 12 G	1.2	37	236	.26	842	.121	7.9
L 15 G	1.5	38	209	.43	655	.118	7.9
L 18 G	1.8	38	190	.59	559	.117	7.9
L 22 G	2.2	38	174	.68	521	.117	7.9
L 27 G	2.7	38	158	.92	448	.116	7.9
L 33 G	3.3	39	142	1.3	377	.115	7.9
L 39 G	3.9	39	132	1.6	339	.115	7.9
L 47 G	4.7	54	81.7	.23	895	.121	7.9
L 56 G	5.6	50	74.4	.27	826	.121	7.9
L 68 G	6.8	57	67.6	.42	662	.118	7.9
L 82 G	8.2	54	62.4	.50	607	.118	7.9
L 100	10	50	56.6	.57	569	.118	7.9
L 120	12	76	50.2	.90	453	.116	2.5
L 150	15	82	44.7	1.3	377	.115	2.5
L 180	18	82	41.3	1.6	339	.115	2.5

- All choke coils in this series are the same size as the unit illustrated.
- Leads are of No. 21 tinned wire.
- Values from 1.0 uh to 3.9 uh are wound on phenolic forms.
- Values from 4.7 uh to 18 uh are wound on iron core forms.
- Tolerances are +/- 10%.
- All units are impregnated with thermosetting varnish and are EIA color coded.

## Wilco Corporation

6451 Saguro Ct.  
 Indianapolis, IN 46268  
 Hotline 800•611•2343  
 Fax 317•293•9462  
 www.wilcocorp.com